

# A: Datasheet

Algorithm: clearviewai\_002

Developer: Clearview AI Inc

Submission Date: 2024\_06\_18

Template size: 2048 bytes

Template time (2.5 percentile): 771 msec

Template time (median): 787 msec

Template time (97.5 percentile): 795 msec

Investigation:

Frontal mugshot ranking 54 (out of 503) -- FNIR(1600000, 0, 1) = 0.0011 vs. lowest 0.0008 from intema\_001

Mugshot webcam ranking 51 (out of 465) -- FNIR(1600000, 0, 1) = 0.0074 vs. lowest 0.0054 from sensetime\_009

Mugshot profile ranking 17 (out of 434) -- FNIR(1600000, 0, 1) = 0.0550 vs. lowest 0.0510 from nec\_009

Immigration visa-border ranking 28 (out of 392) -- FNIR(1600000, 0, 1) = 0.0009 vs. lowest 0.0005 from psl\_001

Immigration visa-kiosk ranking 41 (out of 336) -- FNIR(1600000, 0, 1) = 0.0491 vs. lowest 0.0387 from cloudwalk\_mt\_002

Identification:

Frontal mugshot ranking 70 (out of 503) -- FNIR(1600000, T, L+1) = 0.0027, FPIR=0.003000 vs. lowest 0.0010 from sensetime\_009


Mugshot webcam ranking 60 (out of 463) -- FNIR(1600000, T, L+1) = 0.0170, FPIR=0.003000 vs. lowest 0.0065 from sensetime\_009

Mugshot profile ranking 31 (out of 433) -- FNIR(1600000, T, L+1) = 0.1387, FPIR=0.003000 vs. lowest 0.0591 from cloudwalk\_mt\_002


Immigration visa-border ranking 43 (out of 391) -- FNIR(1600000, T, L+1) = 0.0037, FPIR=0.003000 vs. lowest 0.0009 from cloudwalk\_mt\_002

Immigration visa-kiosk ranking 23 (out of 336) -- FNIR(1600000, T, L+1) = 0.0661, FPIR=0.003000 vs. lowest 0.0460 from nec\_009


B: Mugshot natural images, identification mode: FNIR(N, L+1, T) vs. most accurate (nec\_009)



C: Evolution of accuracy for CLEARVIEWAI algorithms on three datasets 2018 – present




D: 1:N error tradeoff by dataset and enrollment type. N = 1600000 individuals




E: Dependence of error rates on T by number enrolled identities, N, for Mugshot natural images


N 00640000 01600000 03000000 06000000 12000000



F: FPIR vs. Selectivity for mugshot images, N = 1600000 subjects enrolled with one recent mate




G: FPIR dependence on T by probe type for N = 1600000 subjects




# H: Reduced length candidate lists for human review

Dataset is border–border with time–lapse [10,15] YRS with N = 1600000. Probes are 10–15 years later than enrollment image




# I: FNIR and FPIR dependence on threshold


Dataset is border-border with time-lapse [10,15] YRS with N = 1600000. Probes are 10-15 years later than enrollment image




J: DET for Mugshot natural images and various N. Links connect points of equal threshold.




# K: Investigational mode: FNIR(N, 1, 0) vs. most accurate (sensetime\_009)



L: Investigational mode: FNIR(1600000, R, 0) by probe type





M: Template duration; search duration vs. N. The blue and pink ribbon covers 95 percent of observed measurements. The template generation time is independent of N. The log and power-law models are fit to the first two (N,T) observations



O: FNIR(T, N = 1.6 million) by sex, age and time-lapse. The top row gives investigational rank-1 miss rates. The bottom panels give high threshold for more lights-out identification with low FPIR.


Algorithm: clearviewai\_002, Dataset: Border-Crossing Ageing N = 1600000  
Text encodes FNIR, Color encodes log(FNIR)



P: FPIR(N = 1.6 million) by sex and age. It is typical for false positive identification rates to be higher in women except in their teens.


Algorithm: clearviewai\_002, Dataset: Border-Crossing Ageing  
Threshold: 0.460273 set to achive FPIR(30-45, Male) = 0.001

Color encodes log(FPIR)



# Q: Identification FNIR(N, T, L+1) and Investigational FNIR(N, 0, R) under ageing

Dataset: 2018 Mugshot N = 3068801



R: Decline of genuine scores with ageing, with some eventually dropping below typical thresholds shown by the horizontal lines

